



F-U 300
 mancal tipo FLANGE
 serviço PESADO
 montagem FIXA

FE-U300
 mancal tipo FLANGE
 serviço PESADO
 montagem EXPANSIVA



Caixa	Eixo		Dimensão nominal (mm)							Expansão Axial (FE-U)	Paraf.	Peso (kg)		D	Rolamentos			
	Ø pol	Ø mm	a	e	i	g	l	s	YF(E)-U3			GF(E)-U3	z1		Bi1	z2	Bi2	
F(E)-U305	1	25	117,5	88,9	20,7	14	38,0	14,0	3,2	M12 1/2	1,80	-	62,0	43,7	38	-	-	
F(E)-U306	1-3/16	30	125,5	96,8	26,0	16	42,0	14,0	3,2	M12 1/2	2,10	2,20	72,0	52,0	43,0	58,5	50,0	
F(E)-U307	1-1/4 1-7/16	35	130,0	101,6	28,2	16	46,0	14,0	7,1	M12 1/2	2,70	2,70	80,0	57,2	48,0	61,5	51,6	
F(E)-U308	1-1/2	40	152,5	117,4	29,7	16	50,0	19,0	7,1	M16 5/8	3,80	3,90	90,0	62,7	52,0	67,0	57,1	
F(E)-U309	1-11/16 1-3/4	45	159,0	123,8	34,8	17,5	56,0	19,0	4,8	M16 5/8	4,60	4,80	100,0	69,8	57,0	73,7	58,7	
F(E)-U310	1-7/8 1-15/16	50	165,0	130,2	36,4	17,5	61,0	19,0	4,8	M16 5/8	5,50	5,70	110,0	75,4	61,0	78,4	66,6	
F(E)-U311	2 2-3/16 2-1/4	55	185,5	146,1	40,8	19	65,0	23,0	4,8	M20 3/4	7,50	7,90	120,0	81,8	66,0	86,0	73,0	
F(E)-U312	2-7/16	60	193,5	152,4	43,1	19	71,5	23,0	4,8	M20 3/4	8,70	9,00	130,0	88,1	71,0	91,6	79,4	
F(E)-U314	2-11/16 2-3/4	70	225,5	177,8	59,5	22	87,5	27,0	6,4	M24 7/8	13,60	14,20	150,0	106,5	78,0	117,5	92,1	
F(E)-U315	2-15/16 3	75	230,0	184,1	59,5	22	87,5	27,0	6,4	M24 7/8	15,20	16,20	160,0	109,5	82,0	122,2	100,0	
F(E)-U318	3-7/16 3-1/2	90	279,5	215,9	75,0	32	110,0	27,0	9,5	M24 1	26,30	26,50	190,0	131,0	96,0	174,3	115,9	
F(E)-U320	3-15/16 4	100	308	241,3	80,8	35	115,8	35,0	9,5	M30 1-1/8	35,40	37,30	215,0	146,8	108,0	159,4	128,6	