



G 200

rolamento ESFÉRICO
fixação por COLAR EXCÊNTRICO
serviço NORMAL



Rolamento	Eixo		Dimensão nominal (mm)								ds (mm) (UNF)	Cargas (Kgf)		Peso (Kg)
	Ø pol	Ø mm	D	d1	Bi	L	n	m	Be	W		dinâmica C _r	estática C _{or}	
G 204-12 V22 G 204 V22	3/4	20	47,0	29,0	34,0	43,5	17,0	26,5	16,0	32,4	M6x1 1/4-28	1310	680	0,20
G 205-14 V22 G 205-15 V22 G 205 V22 G 205-16 V22	7/8 15/16 1	25	52,0	34,0	34,8	44,3	17,4	26,9	17,0	37,4	M6x1 1/4-28	1430	800	0,30
G 206-250 V22 G 206-16 V22 G 206-18 V22 G 206 V22 G 206-19 V22 G 206-20 V22	1 1-1/8 1-3/16 1-1/4	30 30	62,0	40,5	36,4	48,3	18,2	30,1	19,0	44,1	M8x1 5/16-24	2000	1140	0,40
G 207-300 V22 G 207-20 V22 G 207-21 V22 G 207-22 V22 G 207 V22 G 207-23 V22	1-1/4 1-5/16 1-3/8 3/5 1-7/16	30 35	72,0	48,0	37,6	51,1	18,8	32,3	20,0	51,1	M8x1 5/16-24	2640	1550	0,60
G 208-350 V22 G 208-23 V22 G 208-24 V22 G 208 V22	1-7/16 1-1/2 40	35 40	80,0	53,0	42,8	56,3	21,4	34,9	21,0	58,0	M8x1 5/16-24	2990	1860	0,80
G 209-24 V22 G 209-25 V22 G 209-400 V22 G 209-26 V22 G 209-27 V22 G 209-28 V22 G 209 V22	1-1/2 1-9/16 40 1-5/8 1-11/16 1-3/4 45	40 45	85,0	57,0	42,8	56,3	21,4	34,9	22,0	63,5	M8x1 5/16-24	3350	2120	0,90
G 210-27 V22 G 210-28 V22 G 210-450 V22 G 210-30 V22 G 210-31 V22 G 210 V22 G 210-32 V22	1-11/16 1-3/4 45 1-7/8 1-15/16 50 2	45 50	90,0	62,0	49,2	62,7	24,6	38,1	23,0	67,2	M8x1 5/16-24	3600	2370	1,05
G 211-31 V22 G 211-500 V22 G 211-32 V22 G 211 V22 G 211-35 V22	1-15/16 2 55 2-3/16	50 55	100,0	69,0	55,4	71,3	27,7	43,6	25,0	74,3	M10x1,25 3/8-24	4400	2980	1,45

Rolamento	Eixo		Dimensão nominal (mm)								ds (mm) (UNF)	Cargas (Kgf)		Peso (Kg)
	Ø pol	Ø mm	D	d1	Bi	L	n	m	Be	W		dinâmica C _r	estática C _{or}	
G 212-550 V22 G 212-35 V22 G 212-36 V22 G 212 V22 G 212-38 V22 G 212-39 V22	2-3/16 2-1/4 2-3/8 2-7/16	55 60	110,0	75,0	61,8	77,7	30,9	46,8	27,0	82,0	M10x1,25 3/8-24	5350	3350	1,90
G 213-600 V22 G 213-40 V22 G 213 V22	2-1/2 65	60 65	120,0	82,0	68,2	85,7	34,1	51,6	28,0	86,0	M10x1,25 3/8-24	5850	4080	2,40
G 214-600 V22 G 214-39 V22 G 214-40 V22 G 215-650 V22 G 214-42 V22 G 214-43 V22 G 214-44 V22 G 214 V22	2-7/16 2-1/2 65 2-5/8 2-11/16 2-3/4	60 65 70	125,0	86,5	68,2	85,7	34,1	51,6	30,0	96,8	M10x1,25 3/8-24	6350	4590	2,65
G 214-650S V22 G 214-43S V22 G214S V22	2-11/16 70	65 70	125,0	86,5	49,0	66,1	21,5	44,6	28,0	96,8	M10x1,25 3/8-24	6350	4590	2,45
G 215-650 V22 G 215-44 V22 G 215-700 V22 G 215-47 V22 G 215 V22	2-3/4 2-15/16 75	65 70 75	130,0	91,5	74,6	92,1	37,3	54,8	30,0	102,0	M10x1,25 3/8-24	6750	5050	2,80
G 215-47S V22 G 215S V22	2-15/16 75	75	130,0	91,5	49,6	67,1	21,5	45,6	28,0	102,0	M10x1,25 3/8-24	6750	5050	2,65
G 216 V22	80	80	140,0	98,0	74,6	95,2	37,3	57,9	33,0	110,0	M12x1,25	7400	5530	3,10
G 216-47S V22 G 216-750S V22 G 216-48S V22 G 216S V22	2-15/16 3 80	75 80	140,0	98,0	53,2	73,8	23,4	50,4	33,0	110,0	M12x1,25 7/16-20	7400	5530	3,40
G 217-800 V22 G 217-55 V22	3-7/16	80	150,0	105,0	65,7	85,7	34,1	51,6	35,0	119,0	M12x1,25 7/16-20	8500	6210	3,70
G 218-55 V22 G 218-56 V22 G 218 V22	3-7/16 3-1/2 90	80 90	160,0	111,0	52,0	69,5	23,0	46,5	37,0	120,0	M12x1,25 7/16-20	9750	7300	3,70
G 220 V22	100	100	180,0	125,5	57,5	75,0	25,5	49,5	36,0	132,0	M12x1,25	11000	8000	5,30
G 224 V22	120	120	215,0	145,0	63,5	85,1	28,5	56,6	42,0	152,0	M12x1,25	13500	11600	6,90