



Rolamento	Eixo		Dimensão nominal (mm)							ds (mm) (UNF)	Cargas (Kgf)		Peso (Kg)
	Ø pol	Ø mm	D	d1	Bi	n	m	Be	G		dinâmica C <sub>r</sub>	estática C <sub>or</sub>	
Y 201 V22 Y 201-08 V22	1/2	12	47,0	29,0	31,0	12,7	18,3	16,0	4,7	M5x0,8 1/4-28	1310	680	0,20
Y 202 V22 Y 202-10 V22	5/8	15	47,0	29,0	31,0	12,7	18,3	16,0	4,7	M5x0,8 1/4-28	1310	680	0,10
Y 203 V22		17	47,0	29,0	31,0	12,7	18,3	16,0	4,7	M5x0,8	1310	680	0,15
Y 204-12 V22 Y 204 V22	3/4	20	47,0	29,0	31,0	12,7	18,3	16,0	4,7	M6x1 1/4-28	1310	680	0,20
Y 205-14 V22 Y 205-15 V22 Y 205 V22 Y 205-16 V22	7/8 15/16 1	25	52,0	34,0	34,0	14,3	19,7	17,0	5,5	M6x1 1/4-28	1430	800	0,20
Y 206-17 V22 Y 206-18 V22 Y 206 V22 Y 206-19 V22 Y 206-20 V22	1-1/16 1-1/8 1-3/16 1-1/4	30	62,0	40,5	38,1	15,9	22,2	19,0	5,5	M6x1 1/4-28	2000	1140	0,30
Y 207-19 V22 Y 207-20 V22 Y 207-21 V22 Y 207-22 V22 Y 207 V22 Y 207-23 V22	1-3/16 1-1/4 1-5/16 1-3/8 1-7/16	35	72,0	48,0	42,9	17,5	25,4	20,0	6,5	M8x1 5/16-24	2640	1550	0,50
Y 208-24 V22 Y 208-25 V22 Y 208 V22	1-1/2 1-9/16	40	80,0	53,0	49,2	19,0	30,2	21,0	8,0	M8x1 5/16-24	2990	1860	0,65
Y 209-26 V22 Y 209-27 V22 Y 209-28 V22 Y 209 V22	1-5/8 1-11/16 1-3/4	45	85,0	57,0	49,2	19,0	30,2	22,0	8,0	M8x1 5/16-24	3350	2120	0,70
Y 210-29 V22 Y 210-30 V22 Y 210-31 V22 Y 210 V22 Y 210-32 V22	1-13/16 1-7/8 1-15/16 2	50	90,0	62,0	51,6	19,0	32,6	23,0	9,0	M10x1,25 3/8-24	3600	2370	0,80

# Y 200

rolamento ESFÉRICO  
fixação por PARAFUSOS  
serviço NORMAL



Rolamento	Eixo		Dimensão nominal (mm)							ds (mm) (UNF)	Cargas (Kgf)		Peso (Kg)
	Ø pol	Ø mm	D	d1	Bi	n	m	Be	G		C <sub>r</sub> dinâmica	C <sub>or</sub> estática	
Y 211-32 V22	2	55	100,0	69,0	55,6	22,2	33,4	25,0	9,0	M10x1,25 3/8-24	4400	2980	1,15
Y 211-34 V22	2-1/8												
Y 211 V22													
Y 211-35 V22	2-3/16												
Y 212-36 V22	2-1/4	60	110,0	75,0	65,1	25,4	39,7	27,0	10,5	M10x1,25 3/8-24	5350	3350	1,55
Y 212-37 V22	2-5/16												
Y 212 V22													
Y 212-39 V22	2-7/16												
Y 213-39 V22	2-7/16	65	120,0	82,0	65,1	25,4	39,7	28,0	12,0	M10x1,25 3/8-24	5850	4080	1,75
Y 213-40 V22	2-1/2												
Y 213 V22													
Y 214-43 V22	2-11/16	70	125,0	86,5	74,6	30,2	44,4	30,0	12,0	M12x1,25 7/16-20	6350	4590	2,00
Y 214-44 V22	2-3/4												
Y 214 V22													
Y 215-46 V22	2-7/8	75	130,0	91,5	77,8	33,3	44,5	30,0	12,0	M12x1,25 7/16-20	6750	5050	2,20
Y 215-47 V22	2-15/16												
Y 215 V22													
Y 215-48 V22	3												
Y 216 V22		80	140,0	98,0	82,6	33,3	49,3	33,0	14,0	M12x1,25 7/16-20	7400	5530	2,80
Y 216-51 V22	3-3/16												
Y 217-52 V22	3-1/4	85	150,0	105,0	85,7	34,1	51,6	35,0	14,0	M12x1,25 7/16-20	8500	6510	3,55
Y 217 V22													
Y 217-55 V22	3-7/16												
Y 218-55 V22	3-7/16	90	160,0	111,0	96,0	39,7	56,3	37,0	14,0	M12x1,25 1/2-20	9750	7300	4,50
Y 218-56 V22	3-1/2												
Y 218 V22													
Y 220 V22		100	180,0	125,5	108,0	42,0	66,0	40,0	16,0	M16x1,5 5/8-18	11000	8000	6,50
Y 220-64 V22	4												