



P-U 300
mancal tipo APOIO
serviço PESADO
montagem FIXA

PE-U 300
mancal tipo APOIO
serviço PESADO
montagem EXPANSIVA

Caixa	Eixo		Dimensão nominal (mm)								Expansão Axial (PE-U300)	Paraf.	Peso (kg)		D	Rolamentos			
	Ø pol	Ø mm	h	a	e	b	s1	s2	g	w			YP(E)-U3	GP(E)-U3		Y 300	G 300	Bi1	m1
P(E)-U305	1	25	47,6	178	140,0	51	14	22	22	94	3,2	M12 1/2	1,8	-	62,0	38	23	-	-
P(E)-U306	1-3/16	30	54,0	210	164,0	57	14	27	24	108	3,2	M12 1/2	2,70	2,80	72,0	43,0	26,0	50,0	32,5
P(E)-U307	1-1/4 1-7/16	35	60,3	235	187,0	60	16	29	25	119	4,8	M16 5/8	3,50	3,50	80,0	48,0	29,0	51,6	33,3
P(E)-U308	1-1/2	40	66,7	257	203,0	67	16	32	32	133	4,8	M16 5/8	5,20	5,30	90,0	52,0	33,0	57,1	37,3
P(E)-U309	1-11/16 1-3/4	45	73,0	261	209,6	76	16	29	33	143	4,8	M16 5/8	5,50	5,70	100,0	57,0	35,0	58,7	38,9
P(E)-U310	1-7/8 1-15/16	50	79,4	283	225,4	80	16	29	35	158	4,8	M16 5/8	7,20	7,40	110,0	61,0	39,0	66,6	42,0
P(E)-U311	2 2-3/16 2-1/4	55	88,9	321	260,4	86	20	32	38	173	4,8	M18 3/4	9,30	9,70	120,0	66,0	41,0	73,0	45,2
P(E)-U312	2-7/16	60	92,1	349	285,8	90	20	35	41	183	4,8	M20 3/4	11,90	12,20	130,0	71,0	45,0	79,4	48,5
P(E)-U314	2-11/16 2-3/4	70	101,6	372	300,0	95	26	41	41	202	4,8	M24 7/8	17,20	17,80	150,0	78,0	47,0	92,1	58,0
P(E)-U315	2-15/16 3	75	108,0	384	304,8	102	26	42	44	211	6,4	M24 7/8	16,80	17,80	160,0	82,0	50,0	100,0	62,7
P(E)-U316		65	115,9	391	311,0	106	27	41	49	229	9,5	M24 7/8	24,00	25,1	170,0	86,0	52,0	106,4	65,9
P(E)-U318	3-7/16 3-1/2	90	130,2	410	327,0	127	27	41	57	256	9,5	M24 1	31,8	32,0	190,0	96,0	56,0	115,9	72,3
P(E)-U320	3-15/16 4	100	144,5	440	368,0	127	27	38	65	281	9,5	M24 1	44,4	46,3	215,0	108,0	66,0	128,6	78,6