



**SNL 30**

Eixo Ød mm	Mancal	Montagem			Cargas (kgf)		Limite Rotação RPM	Dimensão nominal (mm)														Paraf.	Peso (kg)	
		Rolamento	Bucha de Fixação	Anel de Bloqueio	dinâmica C <sub>r</sub>	estática C <sub>or</sub>		h	a	e	e1	b	s1	s2	g	w	l1	l2	Ca	Da	o			t
160	SNL 3036	23036K	H3036	2 FRB 17/280	83000	125000	2600	170,0	510	430	100	180	28	34	70	333	229	240	108	280	14	72	M24	76,9
170	SNL 3038	23038K	H3038	4 FRB 10/290	86500	134000	2400	180,0	530	450	110	190	28	34	75	353	239	246,5	115	290	15	73	M25	79,0
180	SNL 3040	23040K	H3040	4 FRB 10/310	100000	153000	2200	190,0	560	480	120	210	28	34	80	375	260	270	122	310	10	78	M24	99,8
200	SNL 3044	23044K	OH3044H	4 FRB 10/340	122000	186000	2000	210,0	610	510	130	230	35	42	85	411	280	290	130	340	10	91	M30	126,0
220	SNL 3048	23048K	OH3048H	4 FRB 12/360	129000	208000	1900	220,0	640	540	140	240	35	42	90	434	290	300	140	360	12	97	M30	142,0
240	SNL 3052	23052K	OH3052H	2 FRB 22/400	160000	255000	1700	240,0	700	600	150	260	35	42	95	474	310	315	148	400	12	103	M30	189,0
260	SNL 3056	23056K	OH3056H	6 FRB 10/420	173000	285000	1600	260,0	770	650	160	280	42	50	100	516	320	330	166	420	13	108	M36	225,0
280	SNL 3060	23060K	OH3060H	2 FRB 25/460	212000	345000	1500	280,0	790	670	160	280	42	50	105	551	320	330	168	460	16	118	M36	262,0
300	SNL 3064	23064K	OH3064H	6 FRB 10/480	224000	380000	1400	300,0	830	710	190	310	42	50	110	591	350	360	181	480	22	121	M36	315,0
320	SNL 3068	23068K	OH3068H	4 FRB 16/520	270000	455000	1300	320,0	880	750	200	330	42	50	115	631	370	380	197	520	23	130	M36	345,0
340	SNL 3072	23072K	OH3072H	4 FRB 16/540	275000	480000	1200	320,0	880	750	200	330	42	50	115	631	370	380	198	540	23	130	M36	347,0

Esta linha permite montagens para eixos com diâmetros em polegadas.  
 Consulte os Departamentos de Engenharia / Comercial da FRM para verificar as medidas disponíveis e especificar os componentes.

